
Technical Information

January 2008
Supersedes issue dated November 2006

EMM 050502e-02/Page 1 of 4

Dipropylene Glycol Care

Water-miscible, low-volatility solvent and humectant for
applications in cosmetics


The Chemical Company

Personal Care
Ingredients

Nature	Mixture of isomeric 1,2-dipropylene glycol ethers.						
Molecular formula	$C_6H_{14}O_3$						
CAS-No.	25265-71-8						
PRD-No.	30175430						
Specification	See separate document: "Standard Specification (not for regulatory purposes)" available via BASF's WorldAccount: https://worldaccount.basf.com (registered access).						
Properties	Dipropylene glycol is a condensation product of 1,2-propylene glycol. It is a clear, colorless, low-volatility, almost odorless, oily liquid that is miscible with common organic solvents and water. Organic solvents with which it is immiscible or not freely miscible are aliphatic and terpene hydrocarbons. It is less hygroscopic than diethylene and ethylene glycols and less volatile than ethylene glycol.						
Physical data	The following physical data refer to the pure solvent and are not binding for the product that we place on the market. <table> <tr> <td>Molar mass</td> <td>134.17 g/mol</td> </tr> <tr> <td>Boiling point (at 1013 mbar)</td> <td>228.6°C</td> </tr> <tr> <td>Solidification point (at 1013 mbar)</td> <td>-40°C</td> </tr> </table>	Molar mass	134.17 g/mol	Boiling point (at 1013 mbar)	228.6°C	Solidification point (at 1013 mbar)	-40°C
Molar mass	134.17 g/mol						
Boiling point (at 1013 mbar)	228.6°C						
Solidification point (at 1013 mbar)	-40°C						

Analytical methods

Gas chromatography

Reliable results for the gas chromatographic assay can be obtained in practice under the following conditions.

Column	30-m fused silica capillary column DB wax (= crosslinked polyethylene glycol)	
	Film thickness	0.25 µm
	Inner diameter	0.25 mm
Temperatures	Column heater	90°C; for 5 min, isothermal
		90-220°C; 6°C/min
		200°C; for 5 min, isothermal
	Injector	250°C
	FID	250°C
Carrier gas	Helium	pressure 40 kPa
	Split	60 ml/min
	Septum flush	4 ml/m
Sample	0.2 µl injected direct	
Evaluation	Percentage area method (standardized at 100% with due allowance for the water fraction)	

Applications

Examples of potential applications for dipropylene glycol are submitted below, but the list is by no means complete.

- Humectant in applications where particular value is attached to maintaining the moisture content at a constant value regardless of fluctuations in temperature and atmospheric humidity.
- Solubilizer in water-in-oil systems.
- Additive for extractants, e.g. in the separation of aliphatic and aromatic hydrocarbons.

The following typical formulations are intended as a guide and may, of course, be adapted to accommodate local conditions.

Storage

Dipropylene glycol does not attack the metals mostly used in tank construction and can be stored in normal carbon steel tanks and drums. We advise against the use of galvanized containers.

Pumps

Cast-iron and steel centrifugal pumps with a simple slip-seal, e.g. Europac 600/SATGG*, are suitable. The type of cast iron and steel depends on the pressure rating.

Flange seals

An example of a suitable material for seals is chemical-resistant Klingerit®**. Polytetrafluoroethylene (PTFE) is resistant to dipropylene glycol, and the suitability of other plastics must be verified by experiment before they are taken into use.

Safety Data Sheet

A Safety Data Sheet is available.

Labelling

In the light of the information at our disposal, dipropylene glycol is not a hazardous industrial substance in the sense of the EEC "Guidelines on Classification and Labelling".

Note

This document, or any answers or information provided herein by BASF, does not constitute a legally binding obligation of BASF. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It does not relieve our customers from the obligation to perform a full inspection of the products upon delivery or any other obligation. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE.

January 2008

* Manufacturer: Pacific, Wietz & Co., Flaspoete 101, 44388 Dortmund-Lütgendortmund, Germany.

** Manufacturer: Klinger, 66510 Idstein/Taunus, Germany.

